



FOOD PACKAGING MACHINES

the **STARVIEW ADVANTAGE**

FROM MANUAL SHUTTLE, SEMI-AUTOMATIC TO FULLY
AUTOMATIC INLINE FOOD VACUUM & TRAY SEALING MACHINES



AITS-1216
WITH OPTIONAL TRAY FEEDER, PRODUCT LOADING AND UNLOAD WEIGH CHECK



CONSUMER GOODS



FOOD



MEDICAL DEVICE



PHARMACEUTICAL



NUTRACEUTICAL



AFTERMARKET PARTS

Markets we serve everyday

INNOVATIVE PACKAGING MACHINES
www.starviewpackaging.com

FOOD PACKAGING MACHINES

MODELS COMPARAISON

Click on miniature for more information about that series of Packaging Machines



MSTS



MRTS

Type of food packaging machine:	Manual shuttle film to tray	Manual two station rotary film to tray
Maximum tray dimensions	10.5" x 8.5" or 16.5" x 12.5"	16.5" x 12.5"
Number of open load stations:	1	1
Vacuum pump installed:	N/A or Standard with MAP	N/A or Standard with MAP
Maximum tray depth:	3.9" or 4.7"	4.0"
Registered film:	Optional	Optional
Standard in-feed:	N/A	N/A
Standard out-feed:	N/A	N/A
Average cycle speed without MAP:	1-4 or 1-6 cpm	1-6 cpm
Average cycle speed with MAP:	1-4 cpm	1-4 cpm
Electrical:	208-230 Volts / 3PH / 25 Amps	208-240 Volts / 3PH / 20 or 25 Amps



AITS-1216 & 1220



RTS/MAP



RBF & RBFA

Type of food packaging machine:	Automatic inline film to tray	Automatic rotary film to tray	Semi & fully automatic board to tray
Maximum tray dimensions:	10.6" x 17.3" or 10.8" x 18.5"	10.8" x 15.7"	15" x 20"
Number of open load stations:	2 or 6	1	3 or 5
Vacuum pump installed:	Standard	Standard	N/A
Maximum tray depth:	4.3"	4.3"	3.0"
Registered film:	Optional	Optional	Optional
Standard in-feed:	AITS-1216 : 55" / AITS -1220: 80"	N/A	N/A
Standard out-feed:	AITS-1216: 30" / AITS -1220 : 34"	30"	N/A
Average cycle speed without MAP:	1-15 cpm	1-15 cpm	1-18 cpm
Average cycle speed with MAP:	N/A or 1-10 cpm	1-8 cpm	N/A
Electrical:	208-240 Volts / 3PH / 20 or 25 or 30 Amps	208-240 Volts / 3PH / 32 Amps	208-240 Volts / 1PH / 32 Amps or 208-240 Volts / 3PH / 19 Amps



MSTS SERIES MANUAL SHUTTLE FILM TO TRAY FOOD PACKAGING MACHINES



MSTS-1012
WITH OPTIONAL STAND



MSTS-1418

EXPERIENCE
the **STARVIEW**
ADVANTAGE
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555 www.starviewpackaging.com sales@starviewpackaging.com

MSTS SERIES

MANUAL SHUTTLE FILM TO TRAY FOOD PACKAGING MACHINES

YOUR MARKET ... OUR SOLUTIONS

Starview's **MSTS Series** are designed and competitively priced for "fresh counter" packaging, typically a clear or printed film to a preformed tray for food manufacturing companies, catering, grocery stores, delicatessens, etc. The **MSTS Series** is ideal for low to medium production. This series machines can adapt to seal for a wide range of product tray sizes by simply changing the tooling. The **MSTS Series** machines trim the film to the profile of the tray and automatically rewind the scrap web. The **MSTS Series** sealers will provide years of dependable performance with a minimum of maintenance.

For machines capable of higher production rates please consider Starview's **MRTS, RTS** and **AITS Series** machines. Where modified atmosphere packaging for extended shelf life is needed consider any of the machines with MAP capability.

the STARVIEW ADVANTAGE

- A wide range of standard and custom features available to match customer requirements.
- Uses quick-change anodized aluminum tooling.
- Models available with and without modified atmosphere protection (MAP) capability.
- Convenient touch panel controls for operator convenience, accessibility and process repeatability.
- Automatic film feed, seal & trim and scrap rewind for clear or random print film. Registered print film feed optional.
- Stainless steel wash down construction to allow cleaning in a food handling environment.
- Industry leading design, construction, features and customer support.



more on next page

MSTS SERIES SPECIFICATIONS

	MSTS-1012	MSTS-1418	MSTS/MAP-1418
Maximum tray dimensions:	10.4" x 12.8"	16.5" x 12.5"	16.5" x 12.5"
Open loading stations:	1	1	1
Vacuum pump installed:	N/A	N/A	Standard
Profile film trim:	Standard	Standard	Standard
Maximum tray depth:	3.9"	4.7"	4.7"
Average cycle speed:	1-6 cpm	1-6 cpm	1-4 cpm
Electrical:	208-240 Volts / 3 PH / 10 Amps	208-230 Volts / 3 PH / 10 Amps	208-230 Volts / 3 PH / 25 Amps

Specifications and model availability are subject to change without notice.



Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

Copyright 2022 Starview Packaging Machinery, Inc.





MRTS SERIES MANUAL TWO STATION ROTARY FILM TO TRAY FOOD PACKAGING MACHINES



STANDARD MRTS -1418 SERIES MACHINE

EXPERIENCE
the **STARVIEW**
ADVANTAGE
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555 www.starviewpackaging.com sales@starviewpackaging.com

MRTS SERIES

MANUAL TWO STATION ROTARY FILM TO TRAY FOOD PACKAGING MACHINES

YOUR MARKET ... OUR SOLUTIONS

Starview's **MRTS Series** are designed and competitively priced for "fresh counter" packaging, typically a clear or printed film to a preformed tray for food manufacturing companies, catering, grocery stores, delicatessens, etc. The **MRTS Series** is ideal for low to medium production. This series machines can adapt to seal for a wide range of product tray sizes by simply changing the tooling. The **MRTS Series** machines trim the film to the profile of the tray and automatically rewind the scrap web. The MRTS Series sealers will provide years of dependable performance with a minimum of maintenance.

For machines capable of higher production rates please consider Starview's **AIMS** or **RTS4 Series** machines. Where modified atmosphere packaging for extended shelf life is needed consider any of the machines with MAP capability.

the **STARVIEW** **ADVANTAGE**

- A wide range of standard and custom features available to match customer requirements.
- Uses quick-change anodized aluminum tooling.
- Efficient two-station design makes the MRTS Series ideal for medium volume production and work-cell manufacturing. Allows operators to load and unload trays in one station while the second station is being sealed, vacuum pulled and gassed (if MAP) and trimmed.
- Color touch screen HMI for the ultimate in operator convenience, accessibility and process repeatability.
- Automatic film feed, seal & trim and scrap rewind for clear or random print film. Registered print film feed optional.
- Stainless steel wash down construction to allow cleaning in a food handling environment.
- Industry leading design, construction, features and customer support.



more on next page

MRTS SERIES SPECIFICATIONS

	MRTS-1418	MRTS/MAP-1418
Maximum tray dimensions:	14" x 18"	14" x 18"
Open loading stations:	1	1
Vacuum pump installed:	N/A	Standard
Automatic vacuum & gas cycle:	N/A	Standard
Profile film trim:	Standard	Standard
Maximum tray depth:	4.0"	4.0"
Average cycle speed:	1 – 6 cpm	1 – 4 cpm
Electrical:	208-240 Volts / 3 PH / 20 Amps	208-240 Volts / 3 PH / 25 Amps

Specifications and model availability are subject to change without notice.



REQUEST
A
QUOTE

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

Copyright 2022 Starview Packaging Machinery, Inc.





AIMS-1216 & AIMS-1220 SERIES AUTOMATIC INLINE FILM TO TRAY FOOD PACKAGING MACHINES



AIMS-1220
AUTOMATIC INLINE TRAY SEALER SUITABLE
FOR BOTH PAPER & PLASTIC TRAYS



AIMS-1220-3
WITH OPTIONAL UNLOAD
CONVEYOR CODE DATE SYSTEM



AIMS-1216
WITH OPTIONAL TRAY FEEDER,
PRODUCT LOADING AND
UNLOAD WEIGH CHECK

EXPERIENCE
the **STARVIEW**
ADVANTAGE
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555 www.starviewpackaging.com sales@starviewpackaging.com

AITS-1216 & AITS-1220 SERIES

AUTOMATIC INLINE FILM TO TRAY FOOD PACKAGING MACHINES

YOUR MARKET ... OUR SOLUTIONS

Starview's **AITs Series** are designed and competitively priced for "fresh counter" packaging, typically a clear or printed film to a preformed tray for food manufacturing companies, catering, grocery stores, etc. The standard AITS Series machines will produce only sealed packages without a modified atmosphere. The **AITs Series** is ideal for medium production. This series machines can adapt to seal for a wide range of product tray sizes by simply changing the tooling. These machines trim the film to the profile of the tray and automatically rewind the scrap web. The **AITs Series** sealers will provide years of dependable performance with a minimum of maintenance.

For machines capable of higher production rates please consider Starview's larger **AITs-1220** Series machines. Where modified atmosphere packaging for extended shelf life is needed consider any of the machines with MAP capability.



AITs-1220
WITH OPTIONAL ACCUMULATION TABLE

the STARVIEW ADVANTAGE

- A wide range of standard and automation features including fillers, date and lot code printing, etc. available to match customer requirements.
- Single, double and triple inline sealing presses available to increase the machine throughput while minimizing the floor space required for the additional production.
- Automatic tray conveyor system and optional tray feeder to reduce labor and increase machine production rates.
- Uses quick-change anodized aluminum tooling.
- Models available with and without modified atmosphere protection (MAP) capability.
- Convenient touch panel controls for operator convenience, accessibility and process repeatability.
- Automatic film feed, seal & trim and scrap rewind for clear or random print film.
- Registered print film feed optional.
- Stainless steel wash down construction to allow cleaning in a food handling environment.
- Industry leading design, construction, features and customer support.



more on next page

AIMS-1216 & AIMS-1220 SERIES SPECIFICATIONS

	AIMS-1216	AIMS/MAP-1216
Maximum tray dimensions:	10.8" x 17.3"	10.8" x 17.3"
Number of open load stations:	2	2
Vacuum pump installed:	N/A	Standard
Profile film trim:	Standard	Standard
Maximum tray depth:	4.3"	4.3"
Registered film:	Optional	Optional
Standard in-feed:	55"	55"
Standard out-feed:	30"	30"
Average cycle speed no MAP:	1-15 cpm	1-15 cpm
Average cycle speed with MAP:	N/A	1-10 cpm
Electrical	208-240 Volts / 3 PH / 20 Amps	208-240 Volts / 3 PH / 25 Amps

	AIMS-1220	AIMS/MAP-1220
Maximum tray dimensions:	10.8" x 18.5"	10.8" x 18.5"
Number of open load stations:	6	6
Vacuum pump installed:	N/A	Standard
Profile film trim:	Standard	Standard
Maximum tray depth:	4.3"	4.3"
Registered film:	Optional	Optional
Standard in-feed:	80"	80"
Standard out-feed:	34"	34"
Average cycle speed no MAP:	1-15 cpm	1-15 cpm
Average cycle speed with MAP:	N/A	1-10 cpm
Electrical	208-240 Volts / 3 PH / 30 Amps	208-240 Volts / 3 PH / 30 Amps

Specifications and model availability are subject to change without notice.



Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

Copyright 2025 Starview Packaging Machinery, Inc.





RBF & RBFA SERIES SEMI & FULLY AUTOMATIC BOARD TO TRAY FOOD PACKAGING MACHINES



RBF6 FULLY AUTOMATIC MODEL
SHOWN WITH ATTACHED LID FEEDER
AND FINISHED PACKAGE UNLOAD

EXPERIENCE
the **STARVIEW**
ADVANTAGE
INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555 www.starviewpackaging.com sales@starviewpackaging.com

RBF & RBFA SERIES

SEMI & FULLY AUTOMATIC BOARD TO TRAY FOOD PACKAGING MACHINES

YOUR MARKET ... OUR SOLUTIONS

Starview's **RBF & RBFA Series** rotary type heat sealers are designed for medium to higher volume production requirements. These machines are designed for producing all board heat sealable food containers. RBF & RBFA Series machines may also be used for conventional carded blisters, full face blisters and half-clamshell styles as well as applications using Tyvek, foils and other heat sealable lidstock. The RBF & RBFA Series units are available in six (6) station designs with a standard sealing area of 15 x 20 inches. Other sealing areas are available on request.

The standard RBF Series machines have one sealing station with the remaining five (5) stations used for tray loading and unloading. The RBFA Series machines feature one sealing station, one lid feeding station and one finished package unloading station with the remaining three (3) stations used for tray loading.

the **STARVIEW** **ADVANTAGE**

- A wide range of standard and custom features available to match customer requirements.
- AC Variable frequency precision cam index rotary table drive for smooth table operation and position repeatability.
- Standard Lid feeder and finished package unloader on RBFA models and optional finished package unloader on RBF models increase the machine versatility and lowers labor costs.
- Uses quick-change anodized aluminum tooling.
- Convenient touch screen controls for operator convenience, accessibility and process repeatability.
- A Starview exclusive remote access via standard Ethernet hardwire or optional Wi-Fi router gives management access to real-time process information from the machine.
- Starview's exclusive selectable sealing station program allows the use of one (1) through six (6) sealing fixtures with operator selected start position from HMI.
- Stainless steel wash down construction to allow cleaning in a food handling environment.
- Industry leading design, construction, features and customer support.



more on next page

RBF & RBFA SERIES SPECIFICATIONS

	RBF6-1520	RBF6A-1520
Maximum tray dimensions:	15" x 20"	15" x 20"
Number of open stations:	5	3
Lid feeder:	N/A	Standard
Finished package unloader:	Optional-attached	Standard
Maximum tray depth:	3.0"	3.0"
Average cycle speed:	1 – 18 cpm	1 – 18 cpm
Electrical:	208-240 Volts / 1 PH / 32 Amps or 208-240 Volts / 3 PH / 19 Amps	208-240 Volts / 1 PH / 32 Amps or 208-240 Volts / 3 PH / 19 Amps

Specifications and model availability are subject to change without notice.



REQUEST
A
QUOTE

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555

www.starviewpackaging.com

sales@starviewpackaging.com

Copyright 2022 Starview Packaging Machinery, Inc.

